

Regulators for Portable Calibration Standards

4



PR 150 Single Stage Calibration Gas Regulator

- Non-Corrosive Service
- Inlet Fitting: CGA-600
- Maximum Inlet Pressure: 500 PSIG
- Outlet Flow Settings: .25 LPM, .5 LPM, 1.0 LPM, 1.5 LPM
- Body: Brass Bar Stock
- Spring Housing Cap: Chrome Plated Brass Bar Stock
- Seat: Teflon[®]
- Piston: Brass
- Piston "O" Rings: Buna-N[®]



PR 160 Single Stage Calibration Gas Regulator

- Non-Corrosive Service
- Inlet Fitting: 5/8" - 18 UNF (C-10)
- Maximum Inlet Pressure: 500 PSIG
- Outlet Flow Settings: .25 LPM, .5 LPM, 1.0 LPM, 1.5 LPM
- Body: Brass Bar Stock
- Spring Housing Cap: Chrome Plated Brass Bar Stock
- Seat: Teflon[®]
- Piston: Brass
- Piston "O" Rings: Buna-N[®]



PR 190 Single Stage Click Style Regulator

- Corrosive and Non-Corrosive Service
- C-10, CGA-180
- Multi Flow Capability: .2 LPM, .3 LPM, .5 LPM, 1.0 LPM, 1.5 LPM, 2.5 LPM, 5.0 LPM, 6.0 LPM
- Body: Aluminum
- Spring Housing Cap: Aluminum
- Nozzle: Aluminum
- Seat: KEL-F
- Seals: Nylon
- Inboard Filter: 50 Micron Sintered Stainless Steel