

316 stainless steel flexible hose **Series 601, 602, 604, and 605**

4

| Description   |
|---|
| Series 601 hoses are constructed of 1/4" I.D. Teflon® lined stainless steel braid, rated for 3000 psig. The 601 hoses are fitted with 1/4" NPT brass end connections; they make excellent economical manifold pigtails. The 602 hoses are fitted with 1/4" NPT stainless steel end connections. |
| The Series 604 hoses are constructed of double braided stainless steel, fitted with stainless steel 1/4" NPT end connections, rated for 3000 psig, and cleaned for oxygen service.  |



**Special Hoses**  
We can provide any of the hoses on this page in different lengths and with a wide variety of end fittings.

| Series 601 and 602  |
|---|
| <ul style="list-style-type: none"> <li>• 1/4" I.D. Teflon® lined 316 stainless steel braided hose</li> <li>• Rated for 3000 psig</li> <li>• 601 1/4" NPT female x 1/4" NPT female</li> <li>601M 1/4" NPT male x 1/4" NPT male</li> <li>601MF 1/4" NPT male x 1/4" NPT female</li> <li>• 602 1/4" NPT female x 1/4" NPT female</li> <li>602M 1/4" NPT male x 1/4" NPT male</li> <li>602MF 1/4" NPT male x 1/4" NPT female</li> <li>• Cleaned for oxygen service</li> </ul> |

| Series 604 and 605   |
|--|
| <ul style="list-style-type: none"> <li>• 1/4" I.D. 316 stainless steel double braided hose (605 Series has protective outer armor to provide greater safety and kink resistance.)</li> <li>• Rated for 3000 psig</li> <li>• 1/4" NPT female or male stainless steel end connections</li> <li>• Cleaned for oxygen service</li> </ul> |

| Ordering Information |          |         |          |         |          |
|----------------------|----------|---------|----------|---------|----------|
| Model                | Length   | Model   | Length   | Model   | Length   |
| 601-2                | 2.0 feet | 602-3   | 3.0 feet | 604-6   | 6.0 feet |
| 601M-2               | 2.0 feet | 602M-3  | 3.0 feet | 604M-6  | 6.0 feet |
| 601MF-2              | 2.0 feet | 602MF-3 | 3.0 feet | 604MF-6 | 6.0 feet |
| 601-3                | 3.0 feet | 602-6   | 6.0 feet | 605-2   | 2.0 feet |
| 601M-3               | 3.0 feet | 602M-6  | 6.0 feet | 605M-2  | 2.0 feet |
| 601MF-3              | 3.0 feet | 602MF-6 | 6.0 feet | 605MF-2 | 2.0 feet |
| 601-6                | 6.0 feet | 604-2   | 2.0 feet | 605-3   | 3.0 feet |
| 601M-6               | 6.0 feet | 604M-2  | 2.0 feet | 605M-3  | 3.0 feet |
| 601MF-6              | 6.0 feet | 604MF-2 | 2.0 feet | 605MF-3 | 3.0 feet |
| 602-2                | 2.0 feet | 604-3   | 3.0 feet | 605-6   | 6.0 feet |
| 602M-2               | 2.0 feet | 604M-3  | 3.0 feet | 605M-6  | 6.0 feet |
| 602MF-2              | 2.0 feet | 604MF-3 | 3.0 feet | 605MF-6 | 6.0 feet |

Cryogenic transfer hoses **Series 607C**

- 1/2" I.D. 316 stainless steel double braided hose with protective outer armor to provide greater safety and kink resistance
- Rated for 2150 psig
- 1/2" 45° flare female stainless steel connections (CGA 295) or 5/8" 45° flare (CGA 440) for oxygen
- Cleaned for oxygen service



**Special Hoses**  
We can provide any of the hoses on this page in different lengths and with a wide variety of end fittings.

| Ordering Information |                        |          |
|----------------------|------------------------|----------|
| Model                | Length                 | Model    |
| 607C-4               | for nitrogen and argon | 4.0 feet |
| 607C-6               | for nitrogen and argon | 6.0 feet |
| 607C-4-440           | for oxygen             | 4.0 feet |
| 607C-6-6440          | for oxygen             | 6.0 feet |