

**Pressure Gauges**



Description	Features
The selection of brass, stainless steel, and monel <sup>®</sup> gauges presented here represent those used on pressure regulators offered in this catalog. They can be used as repair parts or for installation in other systems.	<ul style="list-style-type: none"> <li>• 1/4" NPT lower male connection</li> <li>• Cleaned for oxygen service - brass and stainless steel only</li> </ul>

Ordering Information					
Brass with Brass Case - 2-1/2" Dia.		316 Stainless Steel with Stainless Steel Case - 2-1/2" dia.		Monel <sup>®</sup> with Stainless Steel Case 2-1/2" dia.	
Model	Pressure Range psi	Model	Pressure Range psi	Model	Pressure Range psi
9131-4PM-0015	0-15	9132-4PM-3030	30" 0-30	9133-4PM-0100	0-100
9131-4PM-0030	0-30	9132-4PM-0030	0-30	9133-4PM-0300	0-300
9131-4PM-0060	0-60	9132-4PM-0060	0-60	9133-4PM-1000	0-1000
9131-4PM-0100	0-100	9132-4PM-0100	0-100	9133-4PM-3000	0-3000
9131-4PM-0200	0-200	9132-4PM-0200	0-200		
9131-4PM-0400	0-400	9132-4PM-0400	0-400		
9131-4PM-1000	0-1000	9132-4PM-1000	0-1000		
9131-4PM-2000	0-2000	9132-4PM-2000	0-2000		
9131-4PM-4000	0-4000	9132-4PM-3000	0-3000		
9131-4PM-6000	0-6000	9132-4PM-6000	0-6000		
9131-4PM-7500	0-7500	9132-4PM-10000	0-10000		

Other sizes and ranges available.

**Gauges with Face Seal Fittings**

Description	Features
On some high purity regulators the gauges are connected to the regulator body by using face seal fittings rather than NPT threads.	<ul style="list-style-type: none"> <li>• 1/4" female face seal connection</li> <li>• Dual scale dial psig/bar</li> <li>• Cleaned for oxygen service</li> </ul>

Ordering Information	
316 stainless steel with stainless steel case - 2" dia.	
Model	Pressure Range
9122-4VM-3030	30" vac.-0-30 psig (-1.0-2 bar)
9122-4VM-3060	30" vac.-0-60 psig (-1.0-4 bar)
9122-4VM-3100	30" vac. - 0-100 psig (-1.0-7 bar)
9122-4VM-0200	0-200 psig (0-14 bar)
9122-4VM-0400	0-400 psig (0-28 bar)
9122-4VM-1000	0-1000 psig (0-70 bar)
9122-4VM-4000	0-4000 psig (0-280 bar)

