

Medical Gases

3

Product	Part No.	Purity	Impurity	Maximum	Cylinder Size	Contents	Connection
Nitrogen NF	NIT-USP-XX	≥ 99.0%	CO	< 10 ppm	200	228	580
			O <sub>2</sub>	≤ 1.0%	20	23	960
			Odor:	None	10	14	960
Nitrogen NF Cryogenic Liquid					160L	3690	gas-580
					180L	4110	Liq.-295
Nitrous Oxide USP	N20-USP-XX	≥ 99.0	CO	≤ 10 ppm	200	64 lb	326
			Air	≤ 1.0%	20	6.4 lb	910
			CO <sub>2</sub>	≤ 300 ppm	10	3.9 lb	910
			NO	≤ 1 ppm			
			NO <sub>2</sub>	≤ 1 ppm			
			NH <sub>3</sub>	≤ 25 ppm			
			Halogens H <sub>2</sub> O	≤ 1 ppm ≤ 200 ppm			
Oxygen USP**	OXY-USP-XX	≥ 99.0%	CO	≤ 10 ppm	200	249 cf	540
			CO <sub>2</sub>	≤ 300 ppm	20	25 cf	870
			Odor	None	10	15 cf	870
Oxygen Cryogenic Liquid					160L	4580 cf	Gas-540 Liq-440

XX - Complete the part number with the desired cylinder size listed above.

Recommended Equipment
200 series brass regulator, see page 4.8

Cryogenic Product
See Cryogenic Equipment Section, page 4.130

\*Nonstandard cylinder sizes available upon request

\*\*Oxygen that is produced by the air-liquefaction process is exempt from the requirements of the tests for carbon dioxide and carbon monoxide.