

## Praxair™ Material Safety Data Sheet

### 1. Chemical Product and Company Identification

<b>Product Name:</b> 5% Carbon Dioxide-95% Air Mixture (MSDS No. P-4869-D)	<b>Trade Name:</b> Not applicable
<b>Chemical Name:</b> Carbon Dioxide-Air Mixture	<b>Synonyms:</b> Not applicable
<b>Formula:</b> Mixture of CO <sub>2</sub> and Air	<b>Chemical Family:</b> Not applicable
<b>Telephone:</b>	<b>Company Name:</b> Praxair, Inc. 39 Old Ridgebury Road Danbury CT 06810-5113
<b>Emergencies:</b> 1-800-645-4633* <b>CHEMTREC</b> 1-800-424-9300* <b>Routine:</b> 1-800-PRAXAIR	

*\*Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).*

### 2. Composition / Information on Ingredients

For custom mixtures of this product request a Material Safety Data Sheet for each component. See Section 16 for important information about mixtures.

INGREDIENT NAME	CAS NUMBER	PERCENTAGE	OSHA PEL	ACGIH TLV-TWA
Carbon Dioxide	124-38-9	5.00%	5,000 ppm	5,000 ppm*
Air:				
Oxygen	7782-44-7	19.95%	None currently established	None currently established
Nitrogen	7727-37-9	75.05%	None currently established	Simple asphyxiant

*\*Short Term Exposure Limit (STEL); 15 min, 30,000 ppm*

### 3. Hazards Identification

#### EMERGENCY OVERVIEW

**CAUTION! High-pressure gas.  
Can cause rapid suffocation.  
Can increase respiration and heart rate.  
May cause dizziness and drowsiness.  
Self-contained breathing apparatus may be required by rescue workers.  
Odor: None**

**THRESHOLD LIMIT VALUE:** 5000 ppm TLV-TWA (carbon dioxide), ACGIH (1997). TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

**EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:**

**INHALATION**—Prolonged inhalation causes headache and increased heart and respiration rates. With exertion, may cause breathing difficulty.

**SKIN CONTACT**—No harm expected.

**SWALLOWING**—This product is a gas at normal temperature and pressure.

**EYE CONTACT**—No harm expected.

**EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:** None known.

**OTHER EFFECTS OF OVEREXPOSURE:** None known.

**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:** The toxicology and the physical and chemical properties of this mixture suggest that overexposure is unlikely to aggravate existing medical conditions.

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:** A single study has shown an increase in heart defects in rats exposed to 6% carbon dioxide in air for 24 hours at different times during gestation. There is no evidence that carbon dioxide is teratogenic in humans.

**CARCINOGENICITY:** None of the components of this mixture is listed by NTP, OSHA, or IARC.

<b>4. First Aid Measures</b>
------------------------------

**INHALATION:** No emergency care anticipated.

**SKIN CONTACT:** No emergency care anticipated.

**SWALLOWING:** An unlikely route of exposure. This product is a gas at normal temperature and pressure.

**EYE CONTACT:** No emergency care anticipated.

**NOTES TO PHYSICIAN:** *There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition. Refer to section 16.*

<b>5. Fire Fighting Measures</b>
----------------------------------

<b>FLASH POINT (test method)</b>	Not applicable	<b>AUTOIGNITION TEMPERATURE</b>	Not applicable
<b>FLAMMABLE LIMITS IN AIR, % by volume</b>	<b>LOWER</b>	Not applicable	<b>UPPER</b> Not applicable

**EXTINGUISHING MEDIA:** Oxidizing agent; may accelerate combustion. Use media appropriate for surrounding fire.

**SPECIAL FIRE FIGHTING PROCEDURES:**

**CAUTION! High-pressure gas.** Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool, then move them away from fire area if without risk. Shut off gas flow if without risk. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Oxidizing agent; may accelerate combustion. Heat of fire can build pressure in cylinder and cause it to rupture. No part of cylinder should be subjected to a temperature higher than 125°F (52°C). Cylinders containing this mixture are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.)

**HAZARDOUS COMBUSTION PRODUCTS:** None known.

## 6. Accidental Release Measures

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**CAUTION! High-pressure gas.** Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off flow if without risk. Ventilate area or move cylinder to a well-ventilated area. Test for sufficient oxygen, especially in confined spaces, before allowing reentry.

**WASTE DISPOSAL METHOD:** Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

## 7. Handling and Storage

**PRECAUTIONS TO BE TAKEN IN STORAGE:** Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

**PRECAUTIONS TO BE TAKEN IN HANDLING:** Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. Never apply flame or localized heat directly to any part of the cylinder. High temperatures may damage the cylinder and could cause the pressure relief device to fail prematurely, venting the cylinder contents.

## 8. Exposure Controls/Personal Protection

### VENTILATION/ENGINEERING CONTROLS:

- LOCAL EXHAUST**—Preferred
- MECHANICAL (general)**—Acceptable
- SPECIAL**—Not applicable
- OTHER**—Not applicable

**RESPIRATORY PROTECTION:** None required under normal use; however, if use may result in an oxygen-deficient atmosphere or may generate gases or fumes in hazardous concentrations, then an air-supplied respirator should be used. Respiratory protection must conform to OSHA rules as specified in 29 CFR 1910.134.

**SKIN PROTECTION:** Wear work gloves when handling cylinders.

**EYE PROTECTION:** Wear safety glasses when handling cylinders.

**OTHER PROTECTIVE EQUIPMENT:** Metatarsal shoes for cylinder handling. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. Regardless of protective equipment, never touch live electrical parts.

### 9. Physical and Chemical Properties

<b>MOLECULAR WEIGHT:</b> Not applicable	<b>EXPANSION RATIO:</b> Not applicable
<b>SPECIFIC GRAVITY (air=1):</b> At 70°F (21.1°C) and 1 atm: 1.03	<b>SOLUBILITY IN WATER:</b> % by wt., vol/vol at 32°F (0°C): Negligible
<b>GAS DENSITY:</b> At 70°F (21.1°C) and 1 atm: 0.0772 lbs/ft <sup>3</sup> (1.237 kg/m <sup>3</sup> )	<b>VAPOR PRESSURE:</b> AT 68°F (20°C): Not applicable
<b>PERCENT VOLATILES BY VOLUME:</b> 100	<b>EVAPORATION RATE:</b> Gas, not applicable
<b>BOILING POINT (1 atm):</b> Not available	<b>pH:</b> Not applicable
<b>MELTING POINT (1 atm):</b> Not available	
<b>APPEARANCE, ODOR, AND STATE:</b> Colorless, odorless gas at normal temperature and pressure.	

### 10. Stability and Reactivity

<b>STABILITY:</b>	<b>Unstable</b>	<b>Stable</b>	<b>X</b>
<b>INCOMPATIBILITY (materials to avoid):</b> Flammable materials.			
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> None known.			
<b>HAZARDOUS POLYMERIZATION:</b>	<b>May Occur</b>	<b>Will Not Occur</b>	<b>X</b>
<b>CONDITIONS TO AVOID:</b> None known.			

### 11. Toxicological Information

See section 3.

### 12. Ecological Information

No adverse ecological effects expected. This mixture does not contain any Class I or Class II ozone-depleting chemicals. This mixture is not listed as a marine pollutant by DOT.

### 13. Disposal Considerations

**WASTE DISPOSAL METHOD:** Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

### 14. Transport Information

<b>DOT/IMO SHIPPING NAME:</b> Compressed gases n.o.s. (carbon dioxide, oxygen, nitrogen)	<b>HAZARD CLASS:</b> 2.2
<b>IDENTIFICATION NUMBER:</b> UN 1956	<b>PRODUCT RQ:</b> None
<b>SHIPPING LABEL(s):</b> NONFLAMMABLE GAS	<b>PLACARD (When required):</b> NONFLAMMABLE GAS

**SPECIAL SHIPPING INFORMATION:** Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

### 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

#### U.S. FEDERAL REGULATIONS:

##### EPA (Environmental Protection Agency)

**CERCLA:** Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (40 CFR Parts 117 and 302):

**Reportable Quantity (RQ):** None

**SARA:** Superfund Amendment and Reauthorization Act:

- **SECTIONS 302/304:** Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of extremely hazardous substances (40 CFR Part 355):

**Threshold Planning Quantity (TPQ):** None.

**Extremely Hazardous Substances (40 CFR 355):** None.

- **SECTIONS 311/312:** Require submission of Material Safety Data Sheets (MSDSs) and chemical inventory reporting with identification of EPA hazard categories. The hazard categories for this products are as follows:

IMMEDIATE: Yes

PRESSURE: Yes

DELAYED: No

REACTIVITY: No

FIRE: No

- **SECTION 313:** Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

This mixture does not require reporting under Section 313.

**40 CFR 68:** Risk Management Program for Chemical Accidental Release Prevention: Requires development and implementation of risk management programs at facilities that

manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

The components of this mixture are not listed as regulated substances.

**TSCA:** Toxic Substances Control Act: The components of this mixture are listed on the TSCA inventory.

**OSHA (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION):**

**29 CFR 1910.119 :** Process Safety Management of Highly Hazardous Chemicals: Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

This mixture is not listed in Appendix A as a highly hazardous chemical.

**STATE REGULATIONS:**

**CALIFORNIA:** This product is not listed by California under the Safe Drinking Water Toxic Enforcement Act of 1986 (Proposition 65).

**PENNSYLVANIA:** This product is subject to the Pennsylvania Worker and Community Right-To-Know Act (35 P.S. Sections 7301-7320).

<b>16. Other Information</b>
------------------------------

Read and understand the manufacturer's instructions and the precautionary label on the product.

**OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:** *High pressure gas.* Use piping and equipment adequately designed to withstand pressures to be encountered. *May accelerate combustion.* Keep oil and grease away. Store and use away from flammable materials. *Store and use with adequate ventilation.* Close valve after each use; keep closed even when empty. *Never work on a pressurized system.* If there is a leak, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state and local laws; then repair the leak. *Never ground a compressed gas cylinder or allow it to become part of an electrical circuit.*

**MIXTURES:** When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist, or other trained person when you evaluate the end product.

**HAZARD RATING SYSTEMS:**

**NFPA RATINGS:**

HEALTH = 0  
FLAMMABILITY = 0  
REACTIVITY = 0  
SPECIAL = SA (CGA recommends this to designate simple asphyxiant)

**HMIS RATINGS:**

HEALTH = 0  
FLAMMABILITY = 0  
REACTIVITY = 0

**STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:**

<b>THREADED:</b>	CGA-500
<b>PIN-INDEXED YOKE:</b>	CGA-973
<b>ULTRA-HIGH-INTEGRITY CONNECTION:</b>	Not applicable

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Other connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referenced on the label for this product; you may also obtain copies by calling 1-800-PRAXAIR. Further information about this gas mixture can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 1725 Jefferson Davis Highway, Arlington, VA 22202-4102, Telephone (703) 412-0900.

- AV-1 *Safe Handling and Storage of Compressed Gases*
- P-1 *Safe Handling of Compressed Gases in Containers*
- P-9 *Inert Gases—Argon, Nitrogen, and Helium*
- P-14 *Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmospheres*
- SB-2 *Oxygen-Deficient Atmospheres*
- V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*
- V-7 *Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures*
- *Handbook of Compressed Gases, Third Edition*

Praxair asks users of this product to study this Material Safety Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents and contractors of the information on this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

---

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current Praxair MSDSs for these products, contact your Praxair sales representative or local distributor or supplier. If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14150-7891).

Praxair is a trademark of Praxair Technology, Inc.

Praxair, Inc.  
39 Old Ridgebury Road  
Danbury CT 06810-5113

